

2170 Series

Point of Sale System



The 2170 POS Touch Workstation is an all-in-one system designed to deliver high reliability along with exceptional system performance. The 2170 uses efficient mobile electronics, eliminating the need for an internal system fan and increasing operational uptime. Its quiet operation, bright touch screen and small footprint make it a perfect solution for any retail environment.

Better Reliability

- A truly durable platform that provides the perfect hardware solution for even the toughest retail environments.
- A fan-less design increases overall product dependability by eliminating a potential failure point and provides for quiet system operation.
- A smart design for easy maintenance and quick access to input and output ports, ensuring no interruption to standard operation.
- A true flat LED touch monitor provides a bright, easy-to-read display that consumes less power and delivers increased reliability.

Enhanced Sustainability

- A highly efficient power supply and fan-less design dramatically reduce power consumption.
- The unit is fully RoHS compliant (Restriction of Hazardous Substances Directive).
- The product is manufactured using the ISO's 14001-2004 standard for the implementation and operation of environmental management systems.

Greater Flexibility

- Multiple interface connections provide a platform that supports a wide range of POS peripherals.
- A variety of configuration options are available including an integrated MSR, integrated customer display and customer facing rear video display.
- The compact all-in-one footprint is a perfect fit for space-conscious deployments, as well as for temporary and seasonal store locations.

2170 SERIES FEATURES

technical specifications



SOFTWARE | HARDWARE | SERVICE

UTC RETAIL[™]

100 Rawson Road
Victor, NY 14564
p: 800 349 0546
f: 585 924 1434
www.utcretail.com

PROCESSOR	Intel® D2550 dual-core CPU (1M Cache, 1.86 GHz)
SYSTEM MEMORY	2GB 1600 MHz DDR3 SO-DRAM standard (up to 4GB)
GRAPHICS	Intel® Integrated
LCD MONITOR DISPLAY	15" TFT LCD, 300 nits, 1024 x 768
TOUCHSCREEN	5-wire Resistive
HARD DRIVE	320 GB 2.5" SATA II (Solid State Drive; Optional)
NETWORKING	10/100/1000 Mb Ethernet LAN
RS-232 PORT	4 RS-232 Ports (2 powered)
CASH DRAWER PORT	1 Cash Drawer Port (24V)
USB PORT	4 USB 2.0 Ports
VIDEO PORT	1 VGA Port
CUSTOMER DISPLAY	2-Line X 20 Character VFD (Optional) 8.4" Rear Video Display with Tilt (Optional)
MSR	Integrated ISO 3-Track, Programmable (Optional)
RECEIPT PRINTER	Thermal (Optional)
BARCODE SCANNER	1D or 2D Imager (Optional)
CASH DRAWER	Standard or Compact (Optional)
OPERATING SYSTEM SUPPORT	Microsoft® Windows® 7 Professional, Windows® POSReady 2009, Windows® POSReady 7
DIMENSIONS (WXDXH)	15" x 8.9" x 12.6"
COMPLIANT STANDARDS	UL 60950, FCC Class A, RoHS

For more information or to receive a demonstration of UTC RETAIL solutions, call 800-349-0546 email info@utcretail.com or visit us at www.utcretail.com